

# Pre-assembled manifold station

## HEAT METER - TT-WMZw 1" horizontal

The pre-assembled manifold station consists of a manifold cabinet, a heating circuit manifold and a heat meter installation kit. In the following, it is possible to choose between different versions in order to adapt the station to your individual requirements.

Suitable for:



### Manifold cabinet

TT-VS-110T / 80T - Flush-mounted, Height: 700-880 mm, Depth: 100-198 mm / 80-120 mm

TT-VS-A - Surface-mounted, Height: 564 mm, Depth: 125 mm

### Stainless steel manifold

VA-FBif with flow meters 0-5,0 l/min, can be shut-off

DYNA-if with flow indicator 0-5,0 l/min

Connection variant right or left possible

**Heat meter installation kit TT-WMZs 1"** with heat meter up to 1,5 Qn. Return consisting of 1x ball valve G1" M10, 1x fitting piece for meter\* 110 mm, 1x screwing part. Supply consisting of 1x ball valve G1" M10, 2x fill and drain valves G½", 2x manifold end plug G1", 2x vent valves G½".

### FLUSH-MOUNTED CABINET



| CIRCUITS | UP 110T/80T | WIDTH   | ORDER NO. with VA-FBif | ORDER NO. with DYNA-if |
|----------|-------------|---------|------------------------|------------------------|
| 2        | 7/600       | 575 mm  | 3702204 / 3702208      | 3802204 / 3802208      |
| 3        | 7/600       | 575 mm  | 3703204 / 3703208      | 3803204 / 3803208      |
| 4        | 9/750       | 725 mm  | 3704204 / 3704208      | 3804204 / 3804208      |
| 5        | 9/750       | 725 mm  | 3705204 / 3705208      | 3805204 / 3805208      |
| 6        | 9/750       | 725 mm  | 3706204 / 3706208      | 3806204 / 3806208      |
| 7        | 12/900      | 875 mm  | 3707204 / 3707208      | 3807204 / 3807208      |
| 8        | 12/900      | 875 mm  | 3708204 / 3708208      | 3808204 / 3808208      |
| 9        | 12/900      | 875 mm  | 3709204 / 3709208      | 3809204 / 3809208      |
| 10       | 14/1050     | 1025 mm | 3710204 / 3710208      | 3810204 / 3810208      |
| 11       | 14/1050     | 1025 mm | 3711204 / 3711208      | 3811204 / 3811208      |
| 12       | 14/1050     | 1025 mm | 3712204 / 3712208      | 3812204 / 3812208      |
| 13       | 17/1200     | 1175 mm | 3713204 / 3713208      | 3813204 / 3813208      |
| 14       | 17/1200     | 1175 mm | 3714204 / 3714208      | 3814204 / 3814208      |
| 15       | 17/1200     | 1175 mm | 3715204 / 3715208      | 3815204 / 3815208      |

### SURFACE-MOUNTED CABINET



| CIRCUITS | TT-VS-A | WIDTH   | ORDER NO. with VA-FBif | ORDER NO. with DYNA-if |
|----------|---------|---------|------------------------|------------------------|
| 2        | A-600   | 652 mm  | 3702212                | 3802212                |
| 3        | A-600   | 652 mm  | 3703212                | 3803212                |
| 4        | A-600   | 652 mm  | 3704212                | 3804212                |
| 5        | A-750   | 802 mm  | 3705212                | 3805212                |
| 6        | A-750   | 802 mm  | 3706212                | 3806212                |
| 7        | A-750   | 802 mm  | 3707212                | 3807212                |
| 8        | A-900   | 952 mm  | 3708212                | 3808212                |
| 9        | A-900   | 952 mm  | 3709212                | 3809212                |
| 10       | A-1050  | 1102 mm | 3710212                | 3810212                |
| 11       | A-1050  | 1102 mm | 3711212                | 3811212                |
| 12       | A-1050  | 1102 mm | 3712212                | 3812212                |
| 13       | A-1200  | 1252 mm | 3713212                | 3813212                |

\* Plastic fitting pieces for meters are not suitable for permanent usage.