

Base station TT-KL

Suitable for:



The base station TT-KL enables an optimum temperature control for a maximum of 6 or 10 zones in residential and commercial buildings. It has extensive connection options for actuators and room control units, especially for use in underfloor heating and cooling systems.



TT-KL6 - Example



TT-KL10 - Example

‡ **Connection options:** Up to 6 or 10 thermostats and 15 or 18 actuators.

‡ **Power supply:** 230 V with grounding.

‡ **Pump connection:** 230 V, 6 A.

‡ **Sensor connections:** Option for dew point sensor TBH protection and CO (Change over) signal transmitter.

‡ **External timer:** Option for connecting an external timer.

‡ **Versions:** With or without LED indicators.

Including rail or magnetic holder securely packed in the box for easy installation.

TECHNICAL DATA	TT-KL6-230 PM	TT-KL10-230 PM
Input power	max. 50 VA	max. 50 VA
Fuse	T4AH (230 V)	T4AH (230 V)
Total power	15 actuators: max. 36 W (230 V)	18 actuators: max. 36 W (230 V)
Protection class	IP 20	IP 20
Working ambient temperature	0 - 50 °C	0 - 50 °C
Input temperature limiter / dew point sensor	yes	yes
Pump relay	6 A 200 VA Induction	6 A 200 VA Induction
Effectiveness	NC	NC
Max. room thermostats	6	10
Max. actuators	15	18
Dimensions (WxHxD)	105 x 307 x 54 mm	105 x 307 x 54 mm
ORDER NO.	1011	1015