



Room thermostats

TT-RT - SURFACE-MOUNTED ROOM THERMOSTAT




TECHNICAL DATA	
Housing color	RAL 9010
Electronic connection	Screw clamps 0,33 mm ² up to 1,5 mm ²
Mounting	Surface/ Wall mounting (4-hole mounting in flush-mount. box)
Protection class	IP 30
Safety and EMC	in accordance with DIN EN 60730
Max. switching current	2 A
Control range	1 - 6 (ca. 5 °C to 30 °C)
Hysteresis	approx. 0,5 K with a temperature change of max. 4 K/h
Operating voltage	230 VAC, 50 Hz
Protection class	II, after appropriate installation
ORDER NO.	1100

TT-RTU - FLUSH-MOUNTED ROOM THERMOSTAT



TECHNICAL DATA	
Housing color	RAL 9010
Electronic connection	Screw clamps
Mounting	in flush-mounted box (deep flush-mounted box recommended)
Protection class	IP 30
Safety and EMC	in accordance with DIN EN 60730
Max. switching current	10 A
Control range	1 - 6 (ca. 5 °C to 30 °C)
Hysteresis	approx. 0,5 K with a temperature change of max. 4 K/h
Operating voltage	230 VAC, 50 Hz
Protection class	II, after appropriate installation
ORDER NO.	1101

TT-S 203 - DIGITAL ROOM THERMOSTAT



TECHNICAL DATA	
Display type	LCD
Protection class	IP 30
Max. switching current	2 A
Control range	0 °C bis 40 °C, PI(-Regler)
Operating voltage	230 V, 50 Hz
Energy efficiency class	4
Dimensions (WxHxD)	80 x 104 x 35 mm
Menu	- Weekly program - automatic time change to summer / standard time - programmable absence via integrated calendar - setting two different target temperatures - choice of programming in small intervals, either quarter-hourly, half-hourly or hourly
ORDER NO.	1202