


# Floor heating manifold L-FBif

Suitable for:



**Items delivered:** Set consists of supply and return bar. Sound-insulated holders are supplied loose, including labelling stickers and adjustment instructions, packed in cardboard box.

- **Manifold bar:** Stainless steel AISI 304, rustproof and durable.
- **Dimensions:** DN50 S.S. profile, 1760 mm<sup>2</sup> cross sectional area.
- **Connections:** G1½" internal thread on both sides.
- **Supply:** Flow meters 0-5,0 l/min.
- **Return:** Integrated valves, pre-adjustable, connection thread M30x1,5 mm, with manual adjustment cap, actuator can be retrofitted, K<sub>vs</sub> 2,74.
- **Outlets:** G¾" external threads with Eurocone, distances 50 mm.
- **Pressure rating / system:** PN6 for heating systems with water quality according to VDI 2035.

ORDER NO.

|      |   |
|------|---|
| 3902 | L-FBif 2 for 2 circuits, length: 125 mm   |
| 3903 | L-FBif 3 for 3 circuits, length: 175 mm   |
| 3904 | L-FBif 4 for 4 circuits, length: 225 mm   |
| 3905 | L-FBif 5 for 5 circuits, length: 275 mm   |
| 3906 | L-FBif 6 for 6 circuits, length: 325 mm   |
| 3907 | L-FBif 7 for 7 circuits, length: 375 mm   |
| 3908 | L-FBif 8 for 8 circuits, length: 425 mm   |
| 3909 | L-FBif 9 for 9 circuits, length: 475 mm   |
| 3910 | L-FBif 10 for 10 circuits, length: 525 mm |

|      |   |
|------|---|
| 3911 | L-FBif 11 for 11 circuits, length: 575 mm |
| 3912 | L-FBif 12 for 12 circuits, length: 625 mm |
| 3913 | L-FBif 13 for 13 circuits, length: 675 mm |
| 3914 | L-FBif 14 for 14 circuits, length: 725 mm |
| 3915 | L-FBif 15 for 15 circuits, length: 775 mm |
| 3916 | L-FBif 16 for 16 circuits, length: 825 mm |
| 3917 | L-FBif 17 for 17 circuits, length: 875 mm |
| 3918 | L-FBif 18 for 18 circuits, length: 925 mm |

